

## Description

The HNC-310 non-addressable heat detectors are suitable for connection to 2-wire and 4-wire non-addressable fire detection control and indicating equipment, or to addressable fire detection control and indicating equipment that can accept non-addressable type detectors<sup>1</sup>.

An electronic thermistor sensor provides sensitive rate-of-rise alarm operation, or fixed-temperature operation when the response threshold value is exceeded.

The HNC-310 range of non-addressable detectors provide fire detection and alarm system designers with a Standards-compliant, economical heat detector for property protection applications<sup>2</sup> where smoke or multi-sensor detectors may not be suitable due to environmental conditions.



HNC-310 non-addressable heat detector

## Features

- Advanced algorithms provide excellent detection discrimination
- Durable sensor. No adjustment or replacement required
- Surface-mount device (SMD) circuit board design for stable and reliable operation
- Dual LEDs for 360° visibility
- 2-wire models for DC 12 V and DC 24 V operation
- Remote LED output option available
- 4-wire models available with a N/O alarm relay output
- 4-wire models available with auto-reset function
- Connects to zone monitor for use with addressable control and indicating equipment
- Easy installation. No programming required
- Sleek low-profile housing design
- Low maintenance

## Compliance

HNC-310 heat detectors have the following compliance.

	UL 521 <sup>a</sup>	EN 54-5 <sup>b</sup>	CE
HNC-310-H2	✓	✓	✓
HNC-310-HL	✓	✓	✓
HNC-310-HR	—	—	✓
HNC-310-HA	—	—	✓

<sup>a</sup> UL 521 Heat detectors for fire protective signaling systems

<sup>b</sup> EN 54-5 Fire detection and fire alarm systems. Heat detectors. Point detectors

## Accessories

The following accessories are compatible with HNC-310 heat detectors.

Description	Part number	Datasheet
5-terminal 102 mm low profile base	CN3023	31-0035
5-terminal 102 mm low profile base <sup>a</sup>	CN3021	31-0035
9-terminal 102 mm low profile base	CN3043	31-0037
9-terminal 102 mm low profile base <sup>a</sup>	CN3041	31-0037
Detector monitor module	620-001	31-0027
Remote indicator <sup>b</sup>	681-001	31-0034

<sup>a</sup> UL-approved.

<sup>b</sup> Requires 9-terminal base.

<sup>1</sup> May be used with the 620-001 detector monitor module.

<sup>2</sup> **WARNING** – Hazardous levels of smoke and toxic gas can build up before a heat detector might operate. Where life safety and building evacuation is necessary in the event of a fire, smoke, gas or

combination detectors usually provide earlier warning than heat detectors alone.

## Specifications

	HNC-310-H2 HNC-310-H2-U	HNC-310-HL HNC-310-HL-U	HNC-310-HR	HNC-310-HA
Operating voltage	DC (10.8 ~ 33) V		DC (10.8 ~ 26.4) V	
Start-up current	≤ 100 μA			
Start-up time	≤ 30 s			
Quiescent current	40 μA			
Sampling time	(3 ~ 5) s			
Alarm response threshold	59 °C static, and rate-of-rise <sup>a</sup>			
Alarm current (max)	50 mA		30 mA	
Alarm condition indicator	Dual red LEDs			
Remote LED output current (max)	—	15 mA	—	
Alarm relay	—		SPST. N/O. 1.0 A @ DC 30 V / 0.5 A @ AC 125 V	
Reset voltage	≤ 1 V			
Reset time	≤ 5 s			
Auto reset time	—		(4 ~ 6) s	
Operating temperature	(-10 ~ +55)°C			
Operating humidity	(0 ~ 95)% RH, non-condensing			
Storage temperature	(-25 ~ +80)°C			
Storage humidity	(0 ~ 98)% RH, non-condensing			
Dimensions (excluding contacts)	Φ 99 mm × 45 mm			
Ingress protection rating	IP-42			

<sup>a</sup> Detectors are factory-configured for 30 K/min and comply with EN 54-5 class A1 and class A2.

## Ordering Information

	2-Wire	4-Wire	Remote Indicator <sup>a</sup>	Relay Output	Auto Reset
HNC-310-H2 <sup>b</sup>	✓	—	—	—	—
HNC-310-HL <sup>b</sup>	✓	—	✓	—	—
HNC-310-H2-U <sup>c</sup>	✓	—	—	—	—
HNC-310-HL-U <sup>c</sup>	✓	—	✓	—	—
HNC-310-HR	—	✓	—	✓	—
HNC-310-HA	—	✓	—	—	✓

<sup>a</sup> Requires 9-terminal base if remote indicator is installed.

<sup>b</sup> EN type.

<sup>c</sup> UL type.

View the complete range of products at [www.numens.com](http://www.numens.com)

